

## 6M16G330/5e2

## G-Drive Engine Datasheet

Speed	Gross Engine Output		
	COP	PRP	ESP
rpm	kWm	kWm	kWm
1500	223	290	320

### Ratings definitions

	Continuous Power (COP)	Prime Power (PRP)	Standby Power (ESP)
Annual working time	Unlimited	Unlimited	≤200 h
Mean engine load factor	100%	≤70% per 250 h	≤80% per 24 h
Time at full load	Unlimited	≤500 h per year	≤25 h per year
Overload capacity	No	1 h per 12 h (10% overload) ≤25h per year	No

1) The power ratings are in accordance with ISO 3046.

2) Test conditions: 100 kPa, 25 °C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L.

3) The engine maybe operated at : up to 1000m and 30°C without power deration. For sustained operation above these conditions, derate by 3% per 300m, and 2% per 11°C.

4) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

### Basic data

Engine model	6M16G3305/e2	No. of Cylinders/Valves	6/24
Bore×Stroke (mm)	126×130	Displacement (L)	9.726
Fuel system	Mechanical pump	Aspiration	Turbocharged and Intercooled
Compression ratio	17:1	Emission standard	EU Stage II
Overall Dimension (Length×Width×Height) (mm)	1493×822×1206	Engine net weight (kg)	875
Fuel supply advance angle (°)	12		
Flywheel housing	SAE1	Flywheel	11.5"/14"
Max. permitted installing angle (°)	Longitudinal inclination	Front /Rear	10/10
	Cross inclination	Left/Right	45/10
Permitted temperature ambient (°C)	-30-50	Permitted altitude limit (m)	2000
Valve lash/clearance at cold (mm)	(intake valve:0.3) /(exhaust valve:0.4)		

### Performance data

Idle Speed (rpm)	650±50	Max. Speed Limit (rpm)	1545
Mean Piston Speed (m/s)	6.5	BMEP (MPa)	2.632
Friction Power (kW)	/	Fan Power (kW)	12
Load factor	Power (kW)	Fuel consum. g/(kW.h)	Fuel consum. (L/h)
10%	28.9	277.5	9.5
20%	58.0	228.7	15.8
25%	72.4	218.9	18.9
30%	87.1	213.6	22.1
40%	116.1	206.5	28.5
50%	145.2	204.5	35.3
60%	174.2	202.8	42.1
70%	203.3	202.2	48.9
75%	217.9	201.7	52.3
80%	232.4	202.1	55.9
90%	261.5	202.4	63.0
100%	290.3	204.0	70.5

110%	319.5	205.8	78.3
------	-------	-------	------

### Air intake system

Air intake temperature rise (°C)	Permitted difference between turbocharger inlet temperature and ambient temperature (this parameter impacts emission, LAT and altitude capability)	≤15
Air intake resistance (kPa)	Clean filter	≤3.5
	Dirty filter	≤7.5
Needed air flow (kg/h)	Rated Power	1424
	Standby Power	1491
Air filter efficiency		≥99.5%
Recommended Min. diameter of intake pipe (mm)		100

### Intercooler system

Intercooler heat dissipating capacity (kJ/s)	Rated Power	64.2
	Standby Power	73.4
Intercooler efficiency	Rated Power	/
	Standby Power	/
Max. intake temperature when the ambient temperature is 25°C (°C)		55
Permitted temperature difference between intake temperature and ambient temperature (°C)		30
Permitted max. intake pressure drop of intercooler (kPa)		12
Intercooler radiator cooling area (m <sup>2</sup> )		33

### Exhaust system

Permitted Max. exhaust back pressure (kPa)		10-11
Max. exhaust temperature (°C)	Before turbocharger	720
	After turbocharger	550
Exhaust flow (kg/h)	Rated Power	1483
	Standby Power	1557
Recommended Min. diameter of exhaust pipe (mm)		100
Max. bending moment at the turbocharger flange (N·m)		/

### Lubrication system

Volume of oil pan (L)		30
Oil pressure in normal condition (kPa)	Idle speed	130-280
	Rated Power	380-580
Lowest oil pressure alarm valve/highest alarm valve (kPa)		80/1000
Temperature range in main oil passage under rated working condition (°C)		85~105
Max. oil pressure while engine starts (kPa)		1000
Opening pressure of main oil passage pressure limiting valve		450-600
Oil flow (L/min)		136
Oil fuel consumption ratio		≤0.2%

### Noise and Emission

Exhaust smoke (FSN)	Rated working station	≤2.0
	Max. torque working condition	≤2.5
Diesel engine noise (Acoustic power level) (dB(A))		0

### Fuel system

Governor	Electric/Mechanical governor
----------	------------------------------

Steady speed droop		4%-5%
Max. fuel supply resistance of the fuel pump inlet at rated working condition (kPa)		18
Max. fuel return resistance (kPa)		22
Permitted Max. fuel inlet temperature (°C)		70
Fuel supply flow (kg/h)	Rated Power	59.2
	Standby Power	65.7
Min. pressure of fuel pump (kPa)		35
Recommended min. diameter of inlet pipe (mm)		12
Recommended min. diameter of return pipe (mm)		12

#### Electric system

Electric system voltage(V)		24
Starter power/voltage (kW/V)		5.4/24
Alternator power/voltage (kW/V)		1.96/28V
Permitted Max. electric resistance of the starting circuit (Ω)		0.0108
Recommended Min. sectional area of wire (mm <sup>2</sup> )		70
The lowest cold starting temperature (°C)	Without auxiliary starting device	-10
	With auxiliary starting device	-30

#### Cooling system

Water pump Transmission speed ratio		1.26
Permitted Min. coolant temperature when engine working (°C)		40
Coolant fill rate (L/min)		11
Max. time to fill (min)		5
Recommended Min. inside diameter of outlet water pipe(mm)		45
Min. pressure at water pump inlet without degassing device or with some degassing device (kPa)		0
Min. pressure at water pump inlet with full degassing device (kPa)		50
Max. degassing time(min)		25
Coolant capacity of engine (L)		22
Coolant capacity of radiator (L)		28
Water alarm temperature (°C)		100
Thermostat opening temp./ full open temp. (°C)		76/88
Permitted Min. pressure in cooling system		50
Permitted Max. external resistance (at rated speed)		50

#### Heat balance test data (with ambient temperature 43°C )

Pressure of water in/ water out (kPa / kPa)	Rated Power	19/55.1
	Standby Power	24.1/61.2
Coolant flow (m <sup>3</sup> /h)	Rated Power	17.3
	Standby Power	17.3
Temperature of water in/ water out (°C/°C)	Rated Power	77.4/84.3
	Standby Power	80.5/88
Temperature before/after intercooler (°C/°C)	Rated Power	207/45.5
	Standby Power	222.1/47.3
Pressure before /after intercooler (kPa / kPa)	Rated Power	191.9/187.5
	Standby Power	215.3/210.1

Heat taken away by Coolant (kJ/s)	Rated Power	126.8
	Standby Power	136.7
Heat taken away by intercooler (kJ/s)	Rated Power	64.2
	Standby Power	73.4
Heat taken away by exhaust gas (kJ/s)	Rated Power	209.3
	Standby Power	230
Total heat dissipation (kJ/s)		753.6/834.5

### Mounting system

Inertia of flywheel ( $\text{kg}\cdot\text{m}^2$ )	1.75(with connecting plate)
Inertia of crankshaft ( $\text{kg}\cdot\text{m}^2$ )	0.38

### Fuel consum. Curve

