

6M26G500/5e2

G-Drive Engine Datasheet

Speed	Gross Engine Output		
	COP	PRP	ESP
rpm	kWm	kWm	kWm
1500	368	406	447

Ratings definitions

	Continuous Power (COP)	Prime Power (PRP)	Standby Power (ESP)
Annual working time	Unlimited	Unlimited	≤200 h
Mean engine load factor	100%	≤70% per 250 h	≤80% per 24 h
Time at full load	Unlimited	≤500 h per year	≤25 h per year
Overload capacity	No	1 h per 12 h (10% overload) ≤25h per year	No

1) The power ratings are in accordance with ISO 3046.

2) Test conditions: 100 kPa, 25 °C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L.

3) The engine maybe operated at : up to 1000m and 30°C without power deration. For sustained operation above these conditions, derate by 3% per 300m, and 2% per 11°C.

4) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.

Basic data

Engine model	6M26G500/5e2	No. of Cylinders/Valves	6/24
Bore×Stroke (mm)	150×150	Displacement (L)	15.9
Fuel system	Mechanical pump	Aspiration	Turbocharged and Intercooled
Compression ratio	15.7:1	Emission standard	EU Stage II
Overall Dimension (Length×Width×Height) (mm)	2260×1220×1545	Engine net weight (kg)	1900
Fuel supply advance angle (°)	0		
Flywheel housing	SAE 1	Flywheel	14"
Max. permitted installing angle (°)	Longitudinal inclination	Front /Rear	12.5/12.5
	Cross inclination	Left/Right	22.5/22.5
Permitted temperature ambient (°C)	-10-50	Permitted altitude limit (m)	2000
Valve lash/clearance at cold (mm)	(intake valve:0.3±0.03) /(exhaust valve:0.4±0.03)		

Performance data

Idle Speed (rpm)	750±30	Max. Speed Limit (rpm)	1545
Mean Piston Speed (m/s)	7.5	BMEP (MPa)	2.043
Friction Power (kW)	/	Fan Power (kW)	15
Load factor	Power (kW)	Fuel consum. g/(kW.h)	Fuel consum. (L/h)
10%	40.6	311.9	15.1
25%	101.5	227.5	27.5
40%	162.3	210.3	40.6
50%	203.4	206.0	49.9
60%	243.5	200.7	58.2
75%	304.4	196.5	71.2
90%	365.2	195.1	84.8
100%	406.1	196.2	94.9
110%	446.4	198.7	105.6

Air intake system

Air intake temperature rise (°C)	Permitted difference between turbocharger inlet temperature and ambient temperature (this parameter impacts emission, LAT and altitude capability)	5
Air intake resistance (kPa)	Clean filter	≤3
	Dirty filter	≤5
Needed air flow (kg/h)	Rated Power	2454
	Standby Power	2576
Air filter efficiency		≥99.5%
Recommended Min. diameter of intake pipe (mm)		140

Intercooler system

Intercooler heat dissipating capacity (kJ/s)	Rated Power	89.5
	Standby Power	105.5
Intercooler efficiency	Rated Power	≥85%
	Standby Power	≥85%
Max. intake temperature when the ambient temperature is 25°C (°C)		55
Permitted temperature difference between intake temperature and ambient temperature (°C)		30
Permitted max. intake pressure drop of intercooler (kPa)		15
Intercooler radiator cooling area (m ²)		68.9

Exhaust system

Permitted Max. exhaust back pressure (kPa)		7.5
Max. exhaust temperature (°C)	Before turbocharger	750
	After turbocharger	550
Exhaust flow (kg/h)	Rated Power	2535
	Standby Power	2666
Recommended Min. diameter of exhaust pipe (mm)		200
Max. bending moment at the turbocharger flange (N•m)		10

Lubrication system

Volume of oil pan (L)		50
Oil pressure in normal condition (kPa)	Idle speed	≥200
	Rated Power	450~650
Lowest oil pressure alarm valve/highest alarm valve (kPa)		200/1000
Temperature range in main oil passage under rated working condition (°C)		85~105
Max. oil pressure while engine starts (kPa)		1000
Opening pressure of main oil passage pressure limiting valve		550-600
Oil flow (L/min)		≥190 (1500rpm), ≥198 (1800rpm)
Oil fuel consumption ratio		≤0.3%

Noise and Emission

Exhaust smoke (FSN)	Rated working station	≤1.5
	Max. torque working condition	/
Diesel engine noise (Acoustic power level) (dB(A))		115.7

Fuel system

Governor	Electric governor
Steady speed droop	≤3%

Max. fuel supply resistance of the fuel pump inlet at rated working condition (kPa)	13	
Max. fuel return resistance (kPa)	15	
Permitted Max. fuel inlet temperature (°C)	45	
Fuel supply flow (kg/h)	Rated Power	79.67
	Standby Power	88.7
Min. pressure of fuel pump (kPa)	35	
Recommended min. diameter of inlet pipe (mm)	12	
Recommended min. diameter of return pipe (mm)	12	

Electric system

Electric system voltage(V)	24	
Starter power/voltage (kW/V)	8.5/24	
Alternator power/voltage (kW/V)	1.54/28V	
Permitted Max. electric resistance of the starting circuit (Ω)	0.002	
Recommended Min. sectional area of wire (mm ²)	70	
The lowest cold starting temperature (°C)	Without auxiliary starting device	0
	With auxiliary starting device	-10

Cooling system

Water pump Transmission speed ratio	2
Permitted Min. coolant temperature when engine working (°C)	50
Coolant fill rate (L/min)	11
Max. time to fill (min)	8
Recommended Min. inside diameter of outlet water pipe(mm)	45
Min. pressure at water pump inlet without degassing device or with some degassing device (kPa)	50
Min. pressure at water pump inlet with full degassing device (kPa)	0
Max. degassing time(min)	25
Coolant capacity of engine (L)	79
Coolant capacity of radiator (L)	63
Water alarm temperature (°C)	95
Thermostat opening temp./ full open temp. (°C)	77 (1/-2) / 87
Permitted Min. pressure in cooling system	50
Permitted Max. external resistance (at rated speed)	50

Heat balance test data (with ambient temperature 24.8°C)

Pressure of water in/ water out (kPa / kPa)	Rated Power	-37.1/83.7
	Standby Power	-39.0/79.7
Coolant flow (m ³ /h)	Rated Power	38.9
	Standby Power	38.3
Temperature of water in/ water out (°C/°C)	Rated Power	86.2/90.3
	Standby Power	85.7/90.3
Temperature before/after intercooler (°C/°C)	Rated Power	185.0/54.3
	Standby Power	205.0/58.2
Pressure before /after intercooler (kPa / kPa)	Rated Power	216.7/211.9
	Standby Power	240.6/233.8
Heat taken away by Coolant	Rated Power	171.5

(kJ/s)	Standby Power	189.2
Heat taken away by intercooler (kJ/s)	Rated Power	89.5
	Standby Power	105.5
Heat taken away by exhaust gas (kJ/s)	Rated Power	320.4
	Standby Power	349.7
Total heat dissipation (kJ/s)		1005/1118

Mounting system

Inertia of flywheel (kg•m ²)	4.68
Inertia of crankshaft (kg•m ²)	1.71

Fuel consum. Curve

